



1 FLOOR PLAN
SCALE: 1/4" = 1'-0"



2 DOOR DETAIL
SCALE: N.T.S.



DOOR SCHEDULE								
NO.	LOCATION	SIZE	HINGES	HARDWARE	DOOR MATERIAL	FRAME MATERIAL	FINISHES	REMARKS
1	STOREFRONT	(2) 9'-0" X 1'-0" EXISTING ENTRY DOORS		MANUFACT.	1 1/2" S.G. HD.	HM	NA	SEE DOOR NOTE #4, 8, 10
2	SALES AREA / HALLWAY	(1) 9'-0" X 1'-0"		H-1/2 PR.	2 1/2" S.G. HD.	HM	P-4 SALES AREA SIDE P-1 HALLWAY SIDE	SEE DOOR NOTE #1, 2, 3, 1, 9
3	TOILET ROOM	(2) 9'-0" X 1'-0"		H-1/2 PR.	3 1/4" S.G. HD.	HM	P-1 BOTH SIDES	SEE DOOR NOTE #1, 2, 3, 1, 9
4	STOCK ROOM	(1) 9'-0" X 1'-0" EXISTING EGRESS DOOR		H-1/2 PR.	2 1/2" S.G. HD.	HM	P-1 BOTH SIDES	SEE DOOR NOTE #1, 2, 3, 1, 9
5	HALLWAY	(1) 9'-0" X 1'-0" EXISTING EGRESS DOOR		MANUFACT.	4 EXIST.	EXIST.	P-1 ON INTERIOR SIDE MATCH EXTERIOR COLOR ON EXTERIOR SIDE	SEE DOOR NOTE #3, 4, 5
6	STOCK ROOM	(2) 9'-0" X 1'-0" EXISTING EGRESS DOOR		MANUFACT.	4 EXIST.	EXIST.	P-1 ON INTERIOR SIDE MATCH EXTERIOR COLOR ON EXTERIOR SIDE	SEE DOOR NOTE #3, 4, 5

DOOR HARDWARE

HARDWARE SET #1	HARDWARE SET #2	HARDWARE SET #3	HARDWARE SET #4
1 CYLINDER 2 GLASSER 1 TRESHOLD	HASAR RITE 460M EXIT INDICATOR W/ NYL. CYLINDER NORTON 8000 SERIES PUSHMALL HASKIN ALUM. PUSHMALL FINISH TO MATCH EXISTING NIP 602B HALF-SADDLE HILL ALUM.	3 HINGES 1 LATCHSET 1 KICK PLATE 1 DOOR STOP 1 DOOR HOLDER	HASAR 1274 48X64 602 USGSD SCHLAGE NIOSH 800 626 PASSAGE P75 NORTON 8500 X IN 60P GLOSSER OR 200P7H HASKIN 802B 600 KICK PLATE HASKAR 24F 626 DOME STOP UNIVERSAL HASKIN KICK DOWN DOOR HOLDER 2700-2141 MAX. DOOR TO FLOOR CLEARANCE JOHNSTONE KCR-101-K, VINYL, COLOR: 100 CHARCOAL
1 TRANSITION	HASAR 1274 48X64 602 USGSD SCHLAGE NIOSH 800 626 PASSAGE P75 NORTON 8500 X IN 60P GLOSSER OR 200P7H HASKIN 802B 600 KICK PLATE HASKAR 24F 626 DOME STOP UNIVERSAL HASKIN KICK DOWN DOOR HOLDER 2700-2141 MAX. DOOR TO FLOOR CLEARANCE JOHNSTONE KCR-101-K, VINYL, COLOR: 100 CHARCOAL	3 HINGES 1 LATCHSET 1 KICK PLATE 1 DOOR STOP 1 DOOR HOLDER	HASAR 1274 48X64 602 USGSD SCHLAGE NIOSH 800 626 PASSAGE P75 NORTON 8500 X IN 60P GLOSSER OR 200P7H HASKIN 802B 600 KICK PLATE HASKAR 24F 626 DOME STOP UNIVERSAL HASKIN KICK DOWN DOOR HOLDER 2700-2141 MAX. DOOR TO FLOOR CLEARANCE JOHNSTONE KCR-101-K, VINYL, COLOR: 100 CHARCOAL

DOOR NOTES

- THE CONTRACTOR SHALL PROVIDE ALL NECESSARY LABOR, PARTS, AND SUPPORT PRODUCTS FOR A COMPLETE DOOR INSTALLATION. ALL DOOR HANDLE HARDWARE SHALL BE ADA ACCESSIBLE LEVER TYPE (EGLASSE 'ATHENE') STILE OR EQUAL, WITH 626 SATIN GROUND FLAT FINISH. DOOR HARDWARE INCLUDING DOOR HANDLES SHALL MEET ADA REQUIREMENTS.
- DOOR FRAME IS STEEL. SLID FINISHING SHALL BE LINED ON SIDES AND HEAD WITH RIP 2744 STUDS. BRACE TO STRUCTURE ABOVE.
- DOOR TO RECEIVE SLENER AND KICK-PLATE ON THE PUSH SIDE.
- EXIT DOOR SHALL BE OPERABLE WITHOUT USE OF KEYS, SPECIAL KNOWLEDGE OR EFFORT.
- REAR DOOR WITH SIREN LOCK ALARM MODEL 250 BY ALARM NON-REMOVABLE PINS ON HINGE AND NO VISIBLE HARDWARE OUTSIDE FOR HOLLOW METAL DOORS AND FRAMES
- ALL DOORS SHALL HAVE A MIN. CLEAR OPENING WIDTH OF 32".
- DOOR LATCH SHALL BE EQUIPPED WITH LEVER-TYPE HANDLE OR PANG BAR DOOR OPENING HARDWARE SHALL BE MOUNTED BETWEEN 30" OR 44" ABOVE FINISH FLOOR.
- FLOOR AREAS AT EACH SIDE OF ALL DOORS SHALL BE CLEAR AND LEVEL. MAXIMUM THRESHOLD HEIGHTS SHALL BE 1/2". THRESHOLD SHALL PLATE A ENTRY DOOR TO BE COMPATIBLE WITH PORCELAIN TILE INSTALLATION AND HAVE A NON-TAPERED EDGE ON INTERIOR SIDE TO ACCEPT FLUSH PORCELAIN TILE EDGE.
- ALL CYLINDERS ON ALL EXISTING DOORS (IN EXISTING HARDWARE) TO BE CHANGED PER VSP PRODUCT HANDBOOK.
- PROVIDE ADAMS RITE 460M EXIT INDICATOR WITH KEYS CYLINDER ON INTERIOR SIDE. PROVIDE HEADSET SIGN WITH 'L' LETTERS ON CONTRASTING BACKGROUND SIGN STATING "THIS DOOR TO REMAIN UNLOCKED WHEN SPACE IS OCCUPIED".

GENERAL NOTES

ALL MATERIALS USED IN CONSTRUCTION SHALL BE NEW AND OF FIRST CLASS QUALITY.

ALL GYPSUM WALLBOARD USED IN CONSTRUCTION SHALL BE INSTALLED WITH ALL CORNER BEAD TRIMS, ACCESSORIES AND MOLDINGS ECT. AS REQUIRED FOR COMPLETION TAPED AND SANCED READY FOR PAINT BY ORIGINAL CONTRACTOR.

ALL DIMENSIONS ARE FROM FINISH FACE TO FINISH FACE OF ALL NEW MATERIAL UNLESS OTHERWISE SHOWN.

GENERAL CONTRACTOR WILL BE HELD RESPONSIBLE FOR ALL CONSTRUCTION MATERIALS THAT ARE SHIPPED TO THE SITE I.E. LIGHTING FIXTURES, FLOORING MATERIALS ETC. THE COST OF ANY MISSING MATERIALS SHALL BE DEDUCTED FROM THE CONTRACT PRICE AND FINAL PAYMENT. G.C. TO NOTIFY TENANT OF THE SHORTAGE. SHORTAGES SHOULD THERE BE ANY DISCREPANCIES IN INVOICING. G.C. SHALL CHECK ALL PACKING SLIPS UPON ARRIVAL OF ORDERS AND ADVISE TRUCK OF ANY DISCREPANCIES IMMEDIATELY OR G.C. WILL BE HELD RESPONSIBLE.

VERIFY ALL MATERIALS AND COLORS WITH TENANT.

VERIFY DIMENSIONS IN FIELD.

NOTHING SHALL BE PERMITTED TO BE ATTACHED TO SUSPENDED FROM OR PENETRATE ROOF DECK ABOVE. ALL FRAMING AND BRACING SHALL BE FROM TOP CHORD OF JOIST OR STRUCTURAL STEEL.

ALL COLLING TO BE FRAMED AND FINISHED BY G.C.

PRIOR TO TURNOVER OF SPACE TO TENANT, LANDLORD MUST VERIFY WATER-TIGHTNESS OF ENTIRE ROOF SYSTEM INCLUDING ALL PERIMETER FLASHING, INTERNAL/EXTERNAL GUTTER SYSTEMS, PARAPET CORING AND ALL ROOF PENETRATIONS AREAS.

G.C. IS RESPONSIBLE TO VERIFY EXISTING WALLS ARE PLUMB, LEVEL AND SQUARE TO 1/4" IN 10'-0" MAX. AND TO VERIFY SPACE IS SQUARE TO 1/4" IN 10'-0" MAX. IF ANY OF THE WALLS EXCEED THIS TOLERANCE G.C. IS TO BRING THIS TO THE ATTENTION OF THE VITAMIN SHOPPE CONSTRUCTION PROJECT MANAGER IMMEDIATELY FOR DIRECTION AS TO CORRECTIVE ACTION THAT WILL BE REQUIRED.

FOR SEISMAL & FRAMING OF AREA IN FRONT OF VITAMIN SHOPPE LEASE AREA, G.C. TO INSPECT EXISTING SITE CONDITIONS AND INCLUDE IN BID ANY NEW BRACING OR REPLACEMENT OF CONCRETE PER THE FOLLOWING FOR ALL CHIPPED, CRACKED, BROKEN, AND REINFORCED CONCRETE. INCLUDING BUT NOT LIMITED TO:

1. UNEVEN 1/4" OR LESS OR AS-IS.
2. GREATER THAN 1/4" REPAIRS AND REPLACE.

FOR ASPHALT AREAS OR IMMEDIATE PARKING AREA IN FRONT OF STORE, BLACKTOP TO BE SEALED, PATCHED AND SLURRED.

PROVIDE A SEPARATE LINE ITEM PRICING TO VITAMIN SHOPPE PROJECT MANAGER FOR SCOPE OF WORK AS APPLIED.

KNOW BOX TO BE PROVIDED AND INSTALLED BY G.C. AS REQUIRED ON ALL PROJECTS - VERIFY WITH LOCAL AUTHORITIES.

FLOOR PLAN KEY NOTES

- LEASE LINE G.C. TO VERIFY IN FIELD.
- PROVIDE INTERNATIONAL SYMBOL OF ACCESSIBILITY SIGN AT ENTRANCE.
- NOT USED.
- EXISTING ELECTRICAL PANEL. SEE ELECTRICAL SHEETS FOR ADDITIONAL INFORMATION.
- 4000 PHONE BOARD. SEE ELECTRICAL SHEETS FOR MORE INFORMATION.
- EXISTING WINDOW TO RECEIVE WINDOW GRAPHICS BY TENANT VENDOR PRIOR TO INSTALLATION OF NEW INTERIOR WALL. G.C. TO CONFIRM INSTALLATION WITH VENDOR.
- EXISTING WINDOWS TO REMAIN CLEAN AND REPAIR AS NECESSARY.
- G.C. TO VERIFY IF ANY ADDITIONAL FIRE PROOFING OR FIRE CALKING AND/OR MODIFICATIONS ARE REQUIRED BY THE BUILDING DEPARTMENT AND/OR LANDLORD PRIOR TO BID.
- G.C. TO PROVIDE ALL BLOCKING AS REQUIRED FOR SECURING ALL TOILET ROOM ACCESSORIES.
- G.C. TO PROVIDE SLOTTED AIR VENT IN WALL BEYOND. COORDINATE EXACT LOCATION WITH VITAMIN SHOPPE REP.
- G.C. TO PROVIDE AND INSTALL NEW GLAZING FOR STOREFRONT TO MATCH EXISTING. VERIFY EXISTING WINDOW SYSTEM AS NEEDED.
- 2744 PHONE BOARD. SEE ELECTRICAL SHEETS FOR MORE INFORMATION. PAINT P-4 PRIOR TO INSTALLATION.

PARTITION LEGEND

- EXISTING BASE BUILDING WALL. PREPARE TO RECEIVE NEW FINISHES. LEVEL-4 FINISH REQUIRED IN SALES AREA.
 - EXISTING STOREFRONT - PROTECT DURING CONSTRUCTION. CLEAN/REPAIR AS NECESSARY.
 - EXISTING RATED DRIPPING WALL. 6" MIL STUDS AT 16" O.C. WITH R14 INSULATION (MIN) FROM FLOOR TO UNDERSIDE OF DECK ABOVE. LAYER 5/8" TYPE 'X' 6/16" BD. FULL HEIGHT TO EACH SIDE. PREPARED AS REQUIRED TO ACHIEVE R-14 RATING PER UL DESIGN N-465 OR AS OTHERWISE REQUIRED BY CODE. LEVEL-4 FINISH REQUIRED IN SALES AREA.
 - NEW NON-RATED INTERIOR PARTITION. 5/8" MIL STUDS AT 24" O.C. FROM FLOOR TO MIN. 6" ABOVE FIN. GLS. BRACE TOP OF PARTITION DIAGONALLY TO STRUCTURE ABOVE AT MIN. 40" O.C. APPLY LAYER 5/8" TYPE 'X' 6/16" BD. TO INTERIOR SIDE. PREPARED AS REQUIRED TO RECEIVE NEW FINISHES. PROVIDE WATER RESISTANT 5/8" 6/16" BD. TAPED, SPACKLED AND PREPARED AS REQUIRED TO RECEIVE NEW FINISHES. PROVIDE WATER RESISTANT 5/8" 6/16" BD. TAPED, SPACKLED AND PREPARED AS REQUIRED TO RECEIVE NEW FINISHES.
 - NEW NON-RATED INTERIOR PARTITION. 5/8" 20" GA. MIL STUDS AT 16" O.C. FROM FLOOR TO 10' AFF. WITH PLATFORM FOR H.R. HEATER ABOVE. APPLY LAYER WATER RESISTANT 5/8" 6/16" BD. TO EACH SIDE. TAPED, SPACKLED AND PREPARED AS REQUIRED TO RECEIVE NEW FINISHES. PROVIDE WATER RESISTANT 5/8" 6/16" BD. TAPED, SPACKLED AND PREPARED AS REQUIRED TO RECEIVE NEW FINISHES.
 - NEW NON-RATED INTERIOR PARTITION. 6" MIL STUDS AT 24" O.C. FROM FLOOR TO MIN. 6" ABOVE FIN. GLS. BRACE TOP OF PARTITION DIAGONALLY TO STRUCTURE ABOVE AT MIN. 40" O.C. APPLY LAYER 5/8" TYPE 'X' 6/16" BD. TO INTERIOR SIDE. PREPARED AS REQUIRED TO RECEIVE NEW FINISHES. PROVIDE WATER RESISTANT 5/8" 6/16" BD. TO TOILET ROOM SIDE, AND SLOP SINK AREA AND MIN R-14 INSULATION AT ALL PERIMETER WALLS. LEVEL-4 FINISH REQUIRED IN SALES AREA.
 - NEW NON-RATED INTERIOR WALL FINISHING. 5/8" MIL STUDS AT 24" O.C. FROM FLOOR TO MIN. 6" ABOVE FIN. GLS. BRACE TOP OF PARTITION DIAGONALLY TO STRUCTURE ABOVE AT MIN. 40" O.C. APPLY LAYER 5/8" TYPE 'X' 6/16" BD. TO INTERIOR SIDE. TAPED, SPACKLED AND PREPARED AS REQUIRED TO RECEIVE NEW FINISHES. PROVIDE WATER RESISTANT 5/8" 6/16" BD. TO TOILET ROOM SIDE AND SLOP SINK AREA AND MIN R-14 INSULATION AT ALL PERIMETER WALLS. LEVEL-4 FINISH REQUIRED IN SALES AREA.
- NOTE: ALL 6/16" BD. WALLS IN SALES AREA TO HAVE A LEVEL 4 FINISH. PROVIDE TO RECEIVE FINISH AS PER G.C.P.

FREDERICK J. GOGLIA
ARCHITECT, INC. 83P
1800 CRUIS ROAD, SUITE 100
ST. LOUIS, MO 63066
PH: (314) 465-5600 FAX: (314) 465-5600
www.fjg.com



REGISTRATION SEAL

DL	
DU	
REVISIONS	
07/27/14	BUILDING DEPARTMENT COMMENTS
07/27/17	BUILDING DEPARTMENT GENERAL COMMENTS

PROJECT NO. 140542
DATE 07/18/14
DRAWN BY: JGR
STORE NUMBER:
SCALE: AS NOTED

SALES AREA 2,828 S.F.
NON SALES 1,168 S.F.

GROSS AREA 3,996 S.F.

FLOOR PLAN + NOTES

theVitamin Shoppe
230 N. NELLIS BLVD.
LAS VEGAS, NV. 89110